

```

Use :
\*-----*/
void FCM_Main()
{
    // Name: Interrupt, Type: Interrupt: Enable TMR2
    TCCR2B &= 0xf8;
    TCCR2B |= 0x02;
    sei();
    TIMSK2 |= (1 << TOIE2);

    // Name: Loop, Type: Loop: While 1
    while (1)
    {
        // Name: Decision, Type: Decision: count > 5000?
        if (FCV_COUNT > 5000)
        {
            // Name: Output, Type: Output: 1 -> B1
            SET_PORT_PIN(B,1,(1));

            // Name: Delay, Type: Delay: 1 s
            FCI_DELAYBYTE_S(1);

            // Name: Output, Type: Output: 0 -> B1
            SET_PORT_PIN(B,1,(0));

            // Name: Calculation, Type: Calculation:
            // count = 0
            FCV_COUNT = 0;

        } else {
            // Name: Decision, Type: Decision: count > 10?
            if (FCV_COUNT > 10)
            {
                // Name: Output, Type: Output: 1 -> B0
                SET_PORT_PIN(B,0,(1));

                // Name: Delay, Type: Delay: 300 ms
                FCI_DELAYINT_MS(300);

                // Name: Output, Type: Output: 0 -> B0
                SET_PORT_PIN(B,0,(0));

                // Name: Calculation, Type: Calculation:
                // count = 0
                FCV_COUNT = 0;

            } else {
                }
            }
        }
    }
}

```